



<b>Electrical Data</b>		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/354	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
<b>Mechanical Data</b>		
Mechanical range	360	° (continuous)
Torque	max. 0.5	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (A <sub>max</sub> = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

## GL60

### Applications

- Door control system
- Road roller

### Features

- Hollow shaft Ø 6mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

### Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Mechanical end-stop

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Fax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**



<b>Electrical Data</b>		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/340	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
<b>Mechanical Data</b>		
Mechanical range	348	°
Torque	max. 1.5	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

## GL100

### Applications

- Door control system
- Road roller

### Features

- Hollow shaft Ø 10mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

### Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Continuous

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Fax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**



<b>Electrical Data</b>		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/340	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
<b>Mechanical Data</b>		
Mechanical range	346	°
Torque	max. 6	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (A <sub>max</sub> = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

## GL200

### Applications

- Door control system
- Road roller

### Features

- Hollow shaft Ø 20mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

### Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Continuous

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Fax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**



<b>Electrical Data</b>		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/340	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
<b>Mechanical Data</b>		
Mechanical range	348	°
Torque	max. 6	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

## GL300

### Applications

- Door control system
- Road roller

### Features

- Hollow shaft Ø 30mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

### Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Continuous

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Fax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**



<b>Electrical Data</b>		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/340	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
<b>Mechanical Data</b>		
Mechanical range	350	°
Torque	max. 15	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (Amax = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

## GL400

### Applications

- Door control system
- Road roller

### Features

- Hollow shaft Ø 40mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

### Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Continuous

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Fax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**



<b>Electrical Data</b>		
Nominal resistance	5/10	kOhm
Resistance tolerance	±20	%
Independent linearity	±0.25	% of meas. range
Electrical angle	150/340	°
Repeatability	max. 0.1	°
Temperature coefficient of the voltage divider	50	ppm/°C
Recommended wiper current	max. 1	µA
Max. wiper current in case of malfunction	10	mA
Power rating P	max. 0.5	W/40°C
Min. life (electrical)	10 Mio.	cycles
<b>Mechanical Data</b>		
Mechanical range	350	°
Torque	max. 15	Ncm
Min. life (mechanical)	5 Mio.	cycles
Operating temperature	-25 ... +75	°C
Storage temperature	-25 ... +105	°C
Protection class	IP63	
<b>Standards</b>		
Insulating resistance (500 VDC, 1bar, 2s)	10	GOhm
Dielectric strength (VAC, 50Hz, 1min, 1bar)	1	kV
Vibration (A <sub>max</sub> = 0.75mm, f = 30 ... 500 Hz)	10	g
Shock	50	g

## GL500

### Applications

- Door control system
- Road roller

### Features

- Hollow shaft Ø 50mm
- 5 Mio. cycles
- Excellent linearity up to ±0.25%
- Very good resolution, better 0,1°

### Options

- Resistance tolerance ±10%
- Special electrical angles
- Radial cable outlet
- Continuous

Subject to change  
without notice  
State: 27-Oct-2005

Contelec AG  
Portstrasse 38  
CH-2503 Biel/Bienne  
Phone +41 (0)32 3665600  
Fax +41 (0)32 3665604  
sales@contelec.ch

**CONTELEC**